

## DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011  
N.DoP: 1051 - CRM - 05/08/2025

1. Unique identification code of the product-type:	<b>NUOVA NOLA 10</b>					EN
Models:	P64181x (Invicta) - 72410360xxI (CM)					
2. Intended uses:	Residencial space heating appliance fired by wood pellets without hot water supply					
3. Name, registered trade name or registered trade mark and contact address of the manufacturer:	<b>INVICTA</b> <b>Zone Industrielle lieu-dit « la gravette »</b> <b>08350 DONCHERY – FRANCE - Tél: +33 0324 277171</b>					
5. System or systems of assessment and verification of constancy of performance of the construction product:					System 3 and 4	
6. Notified body:	0051 - IMQ S.p.A.					
Test report number:	CS25-0121184-01					
7. Harmonised technical specification:	EN 16510-1:2022 / EN 16510-2-6:2022					
8. Essential characteristics:						
<b>Mechanical resistance and stability</b>						
Maximum load of a chimney the appliance max carry	mchim	20	kg			
<b>Safety in case of fire - Protection of combustible materials</b>						
Minimum distance to combustible materials - bottom	dB	0	mm			
Minimum distance to combustible materials - front floor	dF	1500	mm			
Minimum distance to combustible materials - ceiling	dC	750	mm			
Minimum distance to combustible materials - rear	dR	200	mm			
Minimum distance to combustible materials - side	dS	400	mm			
Minimum distance to combustible materials - lateral radiation	dL	1500	mm			
Minimum distance to combustible materials - frontal radiation	dP	2000	mm			
Thickness of protective insulating material	s	0	mm			
<b>Hygiene, health and the environment - Emission of combustion products</b>						
		<b>nom</b>		<b>part</b>		
Carbon Monoxide emission (CO at 13% O <sub>2</sub> )	CO	78	mg/Nm <sup>3</sup>	289	mg/Nm <sup>3</sup>	
Nitrogen Oxides emission (NO <sub>x</sub> at 13% O <sub>2</sub> )	NO <sub>x</sub>	143	mg/Nm <sup>3</sup>	126	mg/Nm <sup>3</sup>	
Emission of Organic Gaseous Compounds (OGC at 13% O <sub>2</sub> )	OCG	2	mg/Nm <sup>3</sup>	18	mg/Nm <sup>3</sup>	
Particulate Matter emission (PM at 13% O <sub>2</sub> )	PM	5	mg/Nm <sup>3</sup>	10	mg/Nm <sup>3</sup>	
<b>Safety and accessibility in use - Data for installation to a chimney</b>						
		<b>nom</b>		<b>part</b>		
Flue gas outlet temperature	T <sub>s</sub>	251	°C	116	°C	
Minimum flue draught	p	5	Pa	4	Pa	
Flue gas mass flow	Φ <sub>f,g</sub>	6,8	g/s	2,5	g/s	
Fire safety of installation to the chimney - Flue temperature class	Tclass	T200G				
<b>Energy economy and heat retention - Heat output, efficiency and space heating efficiency</b>						
		<b>nom</b>		<b>part</b>		
Heat output	P	9,5	kW	3,0	kW	
Space heat output	PSH	9,5	kW	3,0	kW	
Water heat output, if applicable	PW		kW		kW	
Efficiency	η	88,0	%	94,0	%	
Seasonal space heating efficiency at nominal heat output	η <sub>s</sub>	84	%			
Energy efficiency index	EEI	124	-			
Energy efficiency class	Class		-			
Consumption of electrical auxiliary energy at nominal heat output	elmax	0,058	kW			
Consumption of electrical auxiliary energy at part load heat output	elmin	0,031	kW			
Consumption of electrical auxiliary energy at standby	e <sub>SB</sub>	0,002	kW			
<b>Sustainable use of natural resources</b>						
Environmental sustainability	NDP					
9. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.						
Signed for and on behalf of the manufacturer by					Signature	
Contact Person	Function	Date	Place			
ing. Andrea Tezza	Technical Manager	05/08/2025	Vivier-au-Court			